

## Digital Gauge

# DG50B


# DG100B

# DG155B

# DG205B

**High accuracy, rugged gauges.  
Suitable for installation on machines**

- Magnetic principle
- Excellent resistance to workshop conditions (BP: IP64).  
Resistant to oil, water, dust, vibrations and shocks.
- Accuracy:  $\pm 1 \mu\text{m}$  (DG50BP/50BN),  $\pm 2 \mu\text{m}$  (DG100BP/100BN),  
 $\pm 2.5 \mu\text{m}$  (DG155BP),  $\pm 3 \mu\text{m}$  (DG205BP)
- Resolution:  $0.5 \mu\text{m}$
- Measuring range: 50 mm / 1.96", 100 mm / 3.93",  
155 mm / 6.10" and 205 mm / 8.07"
- High measuring force (DG50BP/100BP)
- Low measuring force (DG50BN/100BN)
- Magnet feeler (DG155BP/205BP)
- Easy installation
- A variety of accessories available (See "Accessories for Gauges")



\*The photo shows DG155BP.

## Specifications

Model	DG50BP	DG50BN	DG100BP	DG100BN	DG155BP	DG205BP
<b>Measuring range</b>	50 mm / 1.96"		100 mm / 3.93"		155 mm / 6.10"	205 mm / 8.07"
<b>Resolution</b>				0.5 $\mu\text{m}$		
<b>Accuracy (at 20 °C / 68 °F)</b>	$\pm 1 \mu\text{m}$		$\pm 2 \mu\text{m}$		$\pm 2.5 \mu\text{m}$	$\pm 3 \mu\text{m}$
<b>Measuring force</b>	Upward All directions: 6.2 N or less	—	All directions: 9.3 N or less	—	$1.8 \pm 0.65 \text{ N}$ $2.7 \pm 0.55 \text{ N}$	—
	Lateral 0.9 ± 0.4 N					
	Downward 1.3 ± 0.5 N					
<b>Protective design grade</b>	Equivalent to IP64	—	Equivalent to IP64	—	Equivalent to IP64	
<b>Sealing (oil, water, dust)</b>	Oil sealing, O-rings, Y-gaskets	—	Oil sealing, O-rings, Y-gaskets	—	Oil sealing, O-rings, Y-gaskets	
<b>Mounting stem diameter</b>		$\varnothing 20^0_{-0.013} \text{ mm}$			$\varnothing 32^0_{-0.05} \text{ mm}$	
<b>Operating temperature</b>			0 °C to 50 °C / 32 °F to 122 °F			
<b>Storage temperature</b>			-20 °C to 60 °C / -4 °F to 140 °F			
<b>Cable length</b>			5m/16.4'			
<b>Feeler</b>	carbide ball tipped feeler (DZ122)		carbide ball tipped feeler (DZ121)		DZ181 carbide ball tipped feeler	
<b>Magnetic feeler</b>	—		—		Attraction force: 10N Lateral slippage force: 2.7N	
<b>Mass (excl. cable unit)</b>	0.35 kg / 0.77 lbs		0.6 kg / 1.32 lbs		1.1 kg / 2.43 lbs	1.3 kg / 2.87 lbs
<b>Option</b>	None	Air lifter DZ-161 mountable	None	Air lifter DZ-161 mountable	None	None

## Dimensions

